

Forstner Bits

SP Z2 V2 RH



537

| D mm | L mm | S mm | | ORDER NO. Right-hand rotation |
|------|------|------|---|----------------------------------|
| 10 | 90 | 8 | 6 | 537.100.31 |
| 12 | 90 | 8 | 6 | 537.120.31 |
| 14 | 90 | 8 | 6 | 537.140.31 |
| 15 | 90 | 8 | 6 | 537.150.31 |
| 16 | 90 | 8 | 6 | 537.160.31 |
| 18 | 90 | 8 | 6 | 537.180.31 |
| 20 | 90 | 8 | 6 | 537.200.31 |
| 22 | 90 | 8 | 6 | 537.220.31 |
| 24 | 90 | 8 | 6 | 537.240.31 |
| 25 | 90 | 8 | 6 | 537.250.31 |
| 26 | 90 | 8 | 6 | 537.260.31 |
| 28 | 90 | 8 | 6 | 537.280.31 |
| 30 | 90 | 8 | 6 | 537.300.31 |
| 32 | 90 | 10 | 6 | 537.320.31 |
| 35 | 90 | 10 | 6 | 537.350.31 |
| 38 | 90 | 10 | 6 | 537.380.31 |
| 40 | 90 | 10 | 6 | 537.400.31 |
| 45 | 90 | 10 | 6 | 537.450.31 |
| 50 | 90 | 10 | 6 | 537.500.31 |
| 55 | 90 | 10 | 6 | 537.550.31 |
| 68 | 157 | 12,7 | 6 | 537.680.31 |
| 70 | 157 | 12,7 | 6 | 537.700.31 |
| 75 | 157 | 12,7 | 2 | 537.750.31 |
| 80 | 157 | 12,7 | 2 | 537.800.31 |
| 85 | 157 | 12,7 | 2 | 537.850.31 |
| 90 | 157 | 12,7 | 2 | 537.900.31 |
| 95 | 157 | 12,7 | 2 | 537.950.31 |
| 100 | 157 | 12,7 | 2 | 537.990.31 |

| D inches | L inches | S inches | | ORDER NO. Right-hand rotation |
|----------|----------|----------|---|----------------------------------|
| 1/4 | 3-35/64 | 3/8 | 6 | 537.064.31 |
| 3/8 | 3-35/64 | 3/8 | 6 | 537.095.31 |
| 1/2 | 3-35/64 | 3/8 | 6 | 537.127.31 |
| 5/8 | 3-35/64 | 3/8 | 6 | 537.158.31 |
| 3/4 | 3-35/64 | 3/8 | 6 | 537.190.31 |
| 7/8 | 3-35/64 | 3/8 | 6 | 537.222.31 |
| 1 | 3-35/64 | 3/8 | 6 | 537.254.31 |
| 1-1/8 | 3-35/64 | 3/8 | 6 | 537.285.31 |
| 1-1/4 | 3-35/64 | 3/8 | 6 | 537.317.31 |
| 1-3/8 | 3-35/64 | 3/8 | 6 | 537.349.31 |
| 1-1/2 | 3-35/64 | 3/8 | 6 | 537.381.31 |
| 1-5/8 | 3-35/64 | 3/8 | 6 | 537.413.31 |
| 1-3/4 | 3-35/64 | 3/8 | 6 | 537.445.31 |
| 1-7/8 | 3-35/64 | 3/8 | 6 | 537.476.31 |
| 2 | 3-35/64 | 3/8 | 6 | 537.508.31 |
| 2-1/8 | 3-35/64 | 3/8 | 6 | 537.540.31 |
| 2-1/4 | 3-35/64 | 3/8 | 6 | 537.571.31 |
| 2-1/2 | 3-35/64 | 3/8 | 6 | 537.635.31 |
| 3 | 3-35/64 | 3/8 | 2 | 537.762.31 |
| 3-1/2 | 3-35/64 | 3/8 | 2 | 537.889.31 |
| 4 | 3-35/64 | 3/8 | 2 | 537.991.31 |
| 4-1/2 | 3-35/64 | 3/8 | 2 | 537.993.31 |

toothed rim $\geq \varnothing 25\text{mm}$



standard rim $< \varnothing 25\text{mm}$

new
new
new
new
new
new
new

STANDARD RIM AND TOOTHED RIM:

Standard rims provide better guidance but tend to overheat. To overcome heat the larger diameters ($\geq \varnothing 25\text{mm}$) are designed with toothed rims.

TECHNICAL DETAILS:

- Long-lasting cutting performance
- Super strength SP steel
- Precision balanced centre point
- 2 ground spurs [V2]
- 2 precision ground cutting edges [Z2].

APPLICATION:

for drilling precise flat bottom holes of any size in softwood. Create oval and arched openings at any angle. Create niches for the installation of brackets/straps, frames/grids.

Forstner Bit Sets

We offer a wide range of Forstner bits in the most popular diameters to execute the cleanest holes for brackets/straps in softwood. Drill ovals and arched openings at any angle for the installation of hinge parts. Available in 4, 5, 7, 12 and 16 bit sets.

537.000.16

SP Z2 V2 RH

- 537.000.04
- 537.000.05
- 537.000.07
- 537.000.12



| DESCRIPTION | SHANK mm | SHANK inches | BIT DIAMETER | | ORDER NO. Right-hand rotation |
|---------------------------------------|----------|--------------|--|---|----------------------------------|
| 5 pcs. Router Bit Set in clamshell | Ø8-10 | | Ø15-20-25-30-35mm | 6 | 537.000.05 |
| 12 pcs. Router Bit Set in clamshell | Ø8-10 | | Ø10-12-14-15-16-18-20-22-25-26-30-35mm | 6 | 537.000.12 |
| 4 pcs. Router Bit Set in clamshell | | Ø3/8 | Ø1/4" - 1/2" - 3/4" - 1" | 6 | 537.000.04 |
| 7 pcs. Router Bit Set in clamshell | | Ø3/8 | Ø1/4" - 3/8" - 1/2" - 5/8" - 3/4" - 7/8" - 1" | 6 | 537.000.07 |
| 16 pcs. Router Bit Set in plastic box | | Ø3/8 | Ø1/4" - 3/8" - 1/2" - 5/8" - 3/4" - 7/8" - 1" - 1-1/8" - 1-1/4" - 1-3/8" - 1-1/2" - 1-5/8" - 1-3/4" - 1-7/8" - 2" - 2-1/8" | 8 | 537.000.16 |